



Green Pin® Bow Shackle BN

Standard bow shackle with safety bolt



Highlights

- ✓ Double safety (cotter pin & safety bolt)
- ✓ Galvanization assures long-term durability
- ✓ Suitable for both one-leg and multi-leg systems
- ✓ Conforms to wide range of certifications (e.g. DNV)
- ✓ Superior stock availability of 99%

Description

The Green Pin® Bow Shackle BN is a bow shackle with a safety bolt. The shackle offers a double safety (split pin and safety bolt) which prevents accidental unscrewing of the pin. Long-term durability is assured due to the galvanization of the Green Pin® Bow Shackle BN. Of course, the Green Pin® Bow Shackle BN conforms to a wide range of certifications from class societies such as DNV GL. The Green Pin® Bow Shackle BN is suitable for both one-leg and multi-leg systems and is available in a range with a working load limit from 0.5 up to 85 ton.

Product details

Productcode	G-4163
Material	bow and pin high tensile steel, Grade 6, quenched and tempered
Safety factor	MBL equals 6 x WLL
Finish	hot dipped galvanized
Certification	2.1 2.2 3.1 MTCa DNV 2.7-1a DNV 2.7-1b DNVGL-ST-0378 CE ABS PDA ABS MA
Standard	EN 13889 and meets performance requirements of US Fed. Spec. RR-C-271, Type IVA, Class 3, Grade A. From 2 t and upward these shackles comply with ASME B30.26

www.greenpin.com



Green Pin® Bow Shackle BN

Technical specifications in inches

Article code	working load limit	Net weight	A diameter bow (inch)	B diameter pin (inch)	C diameter eye (inch)	D width eye (inch)	E width inside (inch)	F length inside (inch)	G width bow (inch)	H length (inch)	I length bolt (inch)	J width (inch)	K thickness nut (inch)	Net weight (LBS)
GPGHMB06	0,5	0.13	1/4	5/16	5/8	9/32	15/32	1 5/32	25/32	1 7/8	1 21/32	1 11/32	5/32	0.13
GPGHMB08	0,75	0.25	5/16	3/8	25/32	11/32	17/32	1 1/4	7/8	2 7/32	1 31/32	1 9/16	3/16	0.25
GPGHMB10	1	0.34	3/8	7/16	29/32	13/32	21/32	1 15/32	1 1/32	2 17/32	2 3/8	1 13/16	5/16	0.34
GPGHMB11	1,5	0.48	7/16	1/2	31/32	7/16	3/4	1 11/16	1 5/32	2 7/8	2 5/8	2	7/16	0.48
GPGHMB13	2	0.92	1/2	5/8	1 11/32	1/2	7/8	2	1 1/4	3 17/32	3 5/32	2 5/16	1/2	0.92
GPGHMB16	3,25	1.62	5/8	3/4	1 9/16	5/8	1 1/16	2 17/32	1 11/16	4 11/32	3 27/32	2 15/16	21/32	1.62
GPGHMB19	4,75	2.59	3/4	7/8	1 13/16	3/4	1 7/32	3	2	5 3/32	4 17/32	3 1/2	3/4	2.59
GPGHMB22	6,5	3.90	7/8	1	2 1/16	7/8	1 13/32	3 9/32	2 9/32	5 21/32	5 1/8	4 1/32	7/8	3.90
GPGHMB25	8,5	5.69	1	1 1/8	2 5/16	31/32	1 11/16	3 3/4	2 11/16	6 15/32	5 29/32	4 21/32	31/32	5.69
GPGHMB28	9,5	8.07	1 1/8	1 1/4	2 5/8	1 3/32	1 27/32	4 1/4	2 15/16	7 5/16	6 17/32	5 5/32	1 1/16	8.07
GPGHMB32	12	10.8	1 1/4	1 3/8	2 7/8	1 1/4	2	4 17/32	3 9/32	7 29/32	7 1/4	5 25/32	1 3/16	10.8
GPGHMB35	13,5	14.4	1 3/8	1 1/2	3 1/8	1 3/8	2 1/4	5 1/4	3 5/8	8 15/16	7 3/4	6 3/8	1 5/16	14.4



Green Pin® Bow Shackle BN

Technical specifications in inches

Article code	working load limit	Net weight	A diameter bow (inch)	B diameter pin (inch)	C diameter eye (inch)	D width eye (inch)	E width inside (inch)	F length inside (inch)	G width bow (inch)	H length (inch)	I length bolt (inch)	J width (inch)	K thickness nut (inch)	Net weight (LBS)
GPGHMB38	17	18.1	1 1/2	1 5/8	3 15/32	1 1/2	2 3/8	5 3/4	3 29/32	9 13/16	7 15/16	6 7/8	3/4	18.1
GPGHMB45	25	30.8	1 3/4	2	4 3/32	1 25/32	2 29/32	7	4 31/32	11 13/16	9 9/16	8 1/2	29/32	30.8
GPGHMB50	35	41.5	2	2 1/4	4 13/32	1 31/32	3 9/32	7 3/4	5 7/16	13 1/16	10 19/32	9 3/8	1 1/32	41.5
GPGHMB57	42,5	62.5	2 1/4	2 9/16	5 3/16	2 1/4	3 3/4	8 3/4	6 5/16	14 7/8	11 27/32	10 23/32	1 5/32	62.5
GPGHMB65	55	87.3	2 1/2	2 3/4	5 23/32	2 9/16	4 1/8	10 1/4	7 3/32	17 1/16	12 15/16	12 7/32	1 1/4	87.3
GPGHMB75	85	137	3	3 1/4	6 9/16	2 15/16	5	13	7 15/32	20 7/8	15	13 3/8	1 17/32	137

www.greenpin.com



Green Pin® Bow Shackle BN

Technical drawing

